



# SciAps X-555 Geochemistry

**The most powerful  
handheld XRF  
ever made!**

- 55 kV operation for superior LODS
- Durable aerospace-grade aluminum frame weighs less than 3 lbs. with battery
- Outstanding thermal dissipation

World's only

**pXRF**

optimized for rare  
earth elements



**Now measure lithium  
in the field!**

SciAps One Box adds the power of LIBS to measure light elements not possible with XRF, including Li, C, Be, F, Na.

For more information, or to schedule a demonstration:

SciAps Inc.  
+1 339.927.9455

**SciAps**

The latest version of SciAps flagship X-500 series delivers the most advanced X-ray tube technology available, led by a 55 kV X-ray tube. It's the world's only handheld XRF with this capability, making it the superior choice for measuring rare earth elements.



## Fast, precise tests

The 55 kV operation, rather than the industry typical 50 kV, delivers superior performance for critical REEs. The 55 kV X-ray tube is essential to measure all of the light REEs: lanthanum, cerium, praseodymium, neodymium, and samarium; plus heavy REEs: europium, gadolinium, and yttrium. Yttrium can be measured by standard XRF analyzers as well, and is a reliable pathfinder for the family of strategic heavy REEs such as dysprosium, thulium and ytterbium.

- Light REEs: La, Ce, Pr, Nd, Sm; and heavy REEs: Eu, Gd, Y
- Transition/pathfinder elements Ti, V, Cr, Mn, Fe, Co, Ni, Cu, Zn, As, Se, Sr, Rb, Zr, Nb, Mo, Te, Ag, Cd, Sn, Sb, Ba
- Heavy metals Ta, W, Au, Hg, Tl, Pb, Bi, U

**55 kV  
X-ray tube**

## A new performance standard

Outstanding heat dissipation allows for high throughput that our customers demand, including core analysis or any application requiring high-volume manual testing. Compatible with third-party data visualization packages including loGAS, Leapfrog. Add benchtop functionality with SciAps Profile Builder PC software — view calibration curves, generate new ones, build highly customized models for your own elements of interest, overlay and compare spectra and more.

## Android platform, SciAps Cloud Services

Familiar Android operating system and app-based software assure quality testing by every operator. Global connectivity with on-board camera Wi-Fi and Bluetooth, with GPS capability for full-featured reporting. Easily manage operations from anywhere with SciAps Cloud Services.



# SciAps X-555 Specifications

**The most powerful  
handheld XRF  
ever made**



### SciAps Test Station

A compact, robust, portable platform for easy testing of hand samples, small cores, powders or even liquids prepared into bags or XRF cups. Operates as a fully interlocked, closed-beam system.



**Optional X-500 Series Kickstand.** Available in the SciAps web store under accessories.

<b>Weight</b>	2.98 lbs. with battery.
<b>Dimensions</b>	8.5" x 9.5" x 2.4"
<b>Excitation Source</b>	5 W X-ray Tube. Max 55 kV, 200 uA. Au anode
<b>Detector</b>	20 mm <sup>2</sup> silicon drift detector (active area), 140 eV resolution FWHM at 5.95 Mn K-alpha line.
<b>Available Apps</b>	Soils, RoHS/WEEE, REE, Mining. New apps are added regularly, please check with company or website.
<b>X-ray Filtering</b>	6 position filter wheel for beam optimization
<b>Environmental Temperature Range</b>	10° F to 130° F at 50% duty cycle.
<b>Analytical Range</b>	36 elements standard, specific elements vary by app. Additional elements may be added upon user request.
<b>Processing Electronics and Host Processing</b>	1.2 GHz quad ARM Cortex A53 64/32-bit; RAM: 2 GB LP-DDR3; Storage: 16 GB eMMC (storage).
<b>Pulse Processor</b>	12 bit with digitization rate of 80 MSPS 8K channel MCA USB 2.0 for high-speed data transfer to host processor. Digital filtering implemented in FPGA for high throughput pulse processing, 20 nS - 24 uS peaking time.
<b>Power</b>	On-board rechargeable Li-ion battery, rechargeable inside device or with external charger, AC power, hot-swap capability (60 s max swap time).
<b>Display</b>	2.7-inch color capacitive touchscreen — 400 MHz Qualcomm Adreno 306 2D/3D graphics accelerator.
<b>Comms/Data Transfer</b>	Wi-Fi, Bluetooth, USB connectivity to most devices, including SciAps Profile Builder PC software.
<b>Calibration</b>	Fundamental parameters. For Geochem and Environmental Soil apps, users may also choose "Compton Normalization" method and/or use empirically derived calibrations.
<b>Calibration Check</b>	External 316 stainless check standard for calibration verification and energy scale validation.
<b>Dual Cameras</b>	Internal high-resolution camera for sample viewing, welds, etc. Macrocamera for photo documentation, reading and storing 2D/3D barcodes and QR codes.
<b>Security</b>	Password protected usage (user level) and internal settings (admin).
<b>Regulatory</b>	CE, RoHS, USFDA registered, Canada RED Act.